



REV. 更改	DESCRIPTION 說明	ENG. 修改人	APPROVE 審核
------------	-------------------	-------------	---------------

**SPECIFICATIONS:**

- 1.Electrical Life:2,000 cycles @ 24VDC 25mA.
- 2.Switching Rating:25mA, 24VDC.
- 3.Non-Switching Rating:100mA, 50VDC.
- 4.Contact Resistance: 50m-ohms max. initial  
100m-ohms max. after life test.
- 5.Insulation Resistance:100M-ohms min. @ 500VDC.
- 6.Dielectric Strength:500VAC 1 minute.
- 7.Capacitance:5pF max.
- 8.Circuit: S.P.S.T
- 9.Terminals:Brass, gold plated.
- 10.Soldering Temperature:Max. 255°C for 5~10 sec.

ITEM NO. 料號	DP10-DM-x-58
----------------	--------------

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF TAIWAY ELECTRONICS LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF TAIWAY ELECTRONICS LTD.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS ANGULAR TOLERANCE: ±1.0°

DIMENSIONS	TOLERANCE
0.00 TO 30.00mm	±0.20mm
30.01 TO 80.00mm	±0.25mm
80.01 TO 150.00mm	±0.30mm
150.01	±0.40mm

MATERIAL

**泰瑋電子有限公司**  
TAIWAY ELECTRONICS COMPONENTS CO.,LTD.

USED 用途 DP10	APPD. 審核 Andy 2006/03/02
FINISH 處理	CHKD. 校對 Andy 2006/03/02
SCALE 比例 3 / 1	UNIT 單位 in(mm)
DR. 製圖 Amy 2006/03/02	
TITLE 名稱 Dip Switches	
DWG NO. 圖號 DM-x-58	
FILE NAME 檔案名稱 DM-xxR.dwg	SHEET 張 1 / 1
	REV. 更改 1

SIZE  
圖紙 A4