



QLSP15USDNG-269
Reverse Mount
Bi-color Red/Green



Product Outline:

This is a reverse mountable bi color LED with AllnGaP Red and InGaN Green. With small footprint and compact size, this package is ideal for status indication.

Features:

- Package in 8mm tape on 7" diameter reel
- Compatible with automatic placement equipment.
- Compliance with EU REACH
- RoHS compliant
- Compatible with infrared and vapor phase reflow solder process.
- Custom Bin available upon special request
- View angel $>120^\circ$
- Color: AllnGaP Red / InGaN Green


Application:

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.

Compliance and Certification:




Mechanical Property: (Dimension)



* All dimensions are in millimeters,
* Tolerances are $\pm 0.10\text{mm}$.

Recommended Solder footprint:



* All dimensions are in millimeters.
* Reflow soldering must not be performed more than twice.



Characteristics

■ Absolute Maximum Ratings

(Ta=25°C)

Color	P _D (mW)	I _F (mA)	I _{FP} * (mA)	T _{OP} (°C)	T _{ST} (°C)	V _R (V)
USD (Red)	50	20	100	-40 ~ 85	-40 ~ 85	5
NG (Green)	80	20	80	-40 ~ 85	-40 ~ 85	5

 *I_{FP}: is pulse @ 1/10 duty cycle and 0.1ms

■ Electrical / Optical Characteristic

(Ta=25 oC)

(AlInGaP RED)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v		180		mcd	I _F =20mA
Peak Wavelength	λ _p		632		nm	
Dominant Wavelength	λ _d		624		nm	
Forward Voltage	V _f		2.0	2.4	V	
View Angle	θ		120		deg	


(InGaN Green)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I _v		300		mcd	I _F =20mA
Peak Wavelength	λ _p		520		nm	
Dominant Wavelength	λ _d		525		nm	
Forward Voltage	V _f		3.3		V	
View Angle	θ		120		deg	

- (1) Tolerance of Dominant Wavelength ±1nm
- (2) Tolerance of measurement: V_F=+/- 0.1V
- (3) Tolerance of Luminous Intensity: ±11%



Characteristic Curves



■ Reliability test:

No	Item	Condition	Time/Cycle	Sample size
1	Steady State Operating Life of Room Temperature	25°C Operating	1000 Hrs	20 pcs
2	Steady State Operating Life of Low Temperature -40°C	-40°C Operating	1000 Hrs	20 pcs
3	Steady State Operating Life of Low Temperature 60°C	60°C Operating	1000 Hrs	20 pcs
4	Steady State Operating Life of Low Temperature 85°C	85°C Operating	1000 Hrs	20 pcs
5	Low temperature storage -40°C	-40°C Storage	1000 Hrs	20 pcs
6	High temperature storage 100°C	100°C Storage	1000 Hrs	20 pcs
7	Steady State Operating Life of High Humidity Heat 60°C 90%	60°C/90% Operating	1000 Hrs	20 pcs
8	Steady State Pulse Operating Life Condition	25°C 10Hz duty=1/10 Operating	200 Cycle	20 pcs
9	Resistance to soldering heat on PCB (JEDEC MSL3)	pre-store@60°C, 60%RH for 52hrs Tslid max.=260 10sec	3 Times	20 pcs
10	Heat Cycle Test (JEDEC MRC)	25°C~65°C~-10°C, 90%RH, 24hr/1cycle	10 Cycle	20 pcs
11	Thermal shock	-40°C / 20min~ 5minr~100°C /20min	300 Cycle	20 pcs


■ Judgment Criteria:

Item	Symbol	Test Condition	Judgment Criteria
Forward Voltage	Vf	R : IF=20 mA	$\Delta V_f < 10\%$
Luminous Flux	Iv		$\Delta I_v < 30\%$



Solder Profile:

-The recommended reflow soldering profile is as follows (temperatures indicated are as measured on the surface of the LED resin):




Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Temperature Min(T_{smin})	100°C	150°C
Temperature Max(T_{smax})	150°C	200°C
Time(t_a) from (T_{smin} to T_{smax})	60-120 seconds	60-120 seconds
Ramp-up rate(T_L to T_p)	3°C/second max.	3°C/second max.
Liquidous Temperature(T_L)	183°C	217°C
Time(t_L) maintained above T_L	60-150 seconds	60-150 seconds
Peak package body temperature(T_p)	235°C	260°C
Time within 5°C of Actual Peak temperature (t_p)	20seconds*	30 seconds*
Ramp-down rate(T_p to T_L)	6°C/second max.	6°C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.




Taping & Packing:




Dim. A	Dim. B	Dim. C	Q'ty/Reel
3.55±0.05	1.35±0.05	0.88±0.05	3K

Unit : mm





Labeling



Ordering Information:

Part #	Multiple Quantities	Quantity per Reel
QLSP15USDNG-269		3000 pcs



Revision History:

Revision Date:	Changes:	Version #:
2-5-2021	Initial release	1.0

